

ADINO PRIMER 327**PRIMER FOR ALL SURFACE****TECHNICAL DATA SHEET****CHARACTERISTICS**

- Reactive primer.
- Improves the adhesion of polyurethane sealants and hybrid sealants on several surfaces.
- Contains solvents.

APPLICATIONS

- Can be used as primer for **ADINO™** products.
- Can be applied on several materials: plastics, concrete, brick, wood, etc.
- In case of porous surfaces, the ADINO Primer 327 should be painted in 2 layers.
- For use on metals, a preliminary test must be done on the material.
- Can also be used to prevent the migration of plasticizers.

TECHNICAL CHARACTERISTICS

Base	Polyurethane
Colour	Black or transparent
Density	0.92 g/cm ³ at 20°C
Viscosity	Ca 50 mPa.s
Drying time	10 - 15 minutes
Flash point	< 21°C
Shelf life after opening	24 h
Shelf life, in the original closed packing between 0°C - +35°C	Min. 12 months

PACKING AND COLOURS

12 cans of 250 ml/box - 27 boxes/pallet
Transparent, black
8 cans of 1 l/box - 27 boxes/pallet
Transparent, black

METHOD OF USE**PREPARATION**

The surface must be dry and free of grease, oil and other dirt.
For use on metals, a preliminary test must be done on the material.

APPLICATION

- Shake the bottle vigorously before use
- Apply with a brush
- After drying (10 - 15 minutes), apply the sealant within a one hour deadline
- In case of porous surfaces, the ADINO Primer 327 should be painted in 2 layers.

STRONGMAN CHEMICALS

Agape World Pvt. Ltd.

A-305, Patel Paradise, Sector- 35E,
Kharghar, Navi Mumbai, PIN: 410210, Maharashtra, India.

E-mail : info@strongmanchemicals.com | Web : www.strongmanchemicals.com |

Customer Care : +91 96197 83727 | Web : www.agape.world |



ADINO PRIMER 327

PRIMER FOR ALL SURFACE

TECHNICAL DATA SHEET

- Make sure the packaging is closed correctly after use. After opening of the bottle, the product must be used within 24 hours.

CLEANING

It is possible to clean with White Spirit within the first 5 minutes. After that a cleaning with MEK is required.

SAFETY

Please refer to safety data sheet which is available on request.

"The information contained herein is offered in good faith based on STRONGMAN CHEMICALS's research and is believed to be accurate. However, because conditions and methods of use of our products are beyond our control, this information shall not be used in substitution for customer's tests to ensure that STRONGMAN CHEMICALS's products are fully satisfactory for your specific applications. STRONGMAN CHEMICALS's sole warranty is that the product will meet its current sales specifications. Your exclusive remedy for breach of such warranty is limited to refund of purchase price or replacement of any product shown to be other than as warranted. STRONGMAN CHEMICALS's specifically disclaims any other expressed or implied warranty of fitness for a particular purpose or merchantability. STRONGMAN CHEMICALS's disclaims liability for any incidental or consequential damages. Suggestions of use shall not be taken as inducements to infringe any patent. Technical indications and data appearing in this brochure are based on our current knowledge and experience and we decline all responsibility for consequences derived from inadequate use. Therefore, our guarantee is limited exclusively to the quality of the product supplied. This technical information can be modified without notice. If necessary request it periodically."

STRONGMAN CHEMICALS

Agape World Pvt. Ltd.

A-305, Patel Paradise, Sector- 35E,

Kharghar, Navi Mumbai, PIN: 410210, Maharashtra, India.

E-mail : info@strongmanchemicals.com | Web : www.strongmanchemicals.com |

Customer Care : +91 96197 83727 | Web : www.agape.world |

